Installation Instructions

Description:	160 Watt 8x10” 2-Way Component Speaker System 2016 - 2023 Toyota Tacoma (Third Generation)
Part Number:	TS1-2810
Assembly Time:	120 Min (2-Hours)

It is always best practice to disconnect your negative battery terminal prior to any electronics installations to avoid damaging the vehicles electrical system. Before you begin, read through these instructions and check that all parts are present.

This installation may require specials skills and tools to complete, it may be necessary to seek a trained installation technician to complete this installation. Please note that MB Quart cannot assume any responsibility for damage resulting from incorrect installation.

TS1-2810 Parts List		
No.	Component Name	Qty
1	8x10" Midrange Woofers	2
2	Tweeters	2
3	Speaker/Crossover Harness	2
4	Tweeter Adapter Plates	2

Tools Required (May Vary on Application)	
1	Bojo or Panel Tool
2	Philips Screwdriver
3	10mm Socket
4	Rachet


OEM Speaker Removal

- Remove the front door top trim by carefully prying with a panel tool.





- Carefully push in the center of the push pin to release the clip and remove.



- Remove the fabric panel in the hand pull pocket.
- Remove the Philips screw at the bottom of the pocket.



TS1-2810 Door Speaker Install

- Using a panel tool remove the cover behind the door latch.

- Remove the Philips screw at the back of the door latch.





- Using a panel tool remove the door switches.

- Then unclip wiring from the switch assembly.





- Starting at the bottom of the door using a panel tool carefully unclip the inner door panel.


- Disconnect the lock and door latch cables from the back of the door panel. Set the door panel aside in a safe location.



OEM Dash Speaker Removal

- Start by disconnecting the speaker wire connector by depressing the preasure tab to release the locking clip. Then, slide the connector out from the speaker basket.

- With the speaker wires removed, you can now remove the (4) 10mm bolts attaching your speakers to the door. Then remove the speaker from the door.



TS1-2810 Door Speaker Install

- To install your speaker, place the speaker into the OEM speaker cut out, and secure it with the previously removed 10mm bolts.

- Next reconnect the OEM speaker wire connector into the correct receptacle on the speaker's basket.

Tech Tip: With your speaker removed, now is a great time to apply sound dampening material around your speaker.



- Now your new speaker is installed, and you can reinstall your door panel in the reverse order.

- Once the door panel is reinstalled. Be sure to test all your window, locks, and door handle functionality. Then repeat on the opposite door.



OEM Dash Speaker Removal

- Using a panel tool pry out the SRS Airbag cover to expose (1) 10mm bolt to remove.





- Pull out on the top of the A-pillar and then pull back toward the rear of the vehicle to remove the panel.




- Remove the top dash speaker cover, in some vehicles it may be necessary to remove the A-pillar panel as well.

- Once the speaker cover is removed place it aside in a safe location.



OEM Dash Speaker Removal

- Remove the (2) 10mm bolt securing the speaker into the top of the dash.
- Disconnect the speaker wire connector from the speaker by depressing the pressure tab releasing the connector locking clip and slide the connector off the speaker.



TS1-2810 Dash Tweeter Install

- On the tweeter plate you will notice a “J” and “T”. You will need to remove the “J” sections.

  Tech Tip: Using a Razor or knife to score the relief groove may assist in a smoother break along the groove.





- With your speaker plate modified to your application, it is time to install the tweeter into the plate. Line up the locking tabs on the tweeter with the cut outs on the inner tweeter hole of the plate, and firmly press it into the plate with the palm of your hand.



- Connect the tweeter wires to the crossover.

- Complete the wiring portion by matching up your OEM speaker wire with the correct connector of the (3) provided on the supplied cross over pigtail.



- Lastly, place all the wires into the speaker cavity and place the tweeter and mounting brackets onto the dash. Line up the 2 mounting holes and secure the new speaker with the OEM 10mm bolt.

- Your new dash speakers are now installed. And you can re assemble your dash in reverse order of how it was taken apart.



FCC Notification

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a mobile installation. This equipment generates uses and can radiate radio frequency energy. If not installed and used in accordance with the instructions, this equipment may cause harmful interference to radio communications. There is no guarantee that interference will not occur in a particular installation.

WARNING: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment complied with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and your body.

MBQuart.com
#MUSIC DEFINED

WARRANTY

Maxxsonics, LLC. warrants this product, to the original consumer purchaser, to be free from defects in material and workmanship for a period of one (1) year from the date of purchase. Maxxsonics, LLC. will, at it's discretion, repair or replace defective products during the warranty period. Components that prove to be defective in materials and workmanship under proper installation and use must be returned to the original authorized Maxxsonics, LLC. retailer from where it was purchased. A photocopy of the original receipt must accompany the product being returned. The costs associated with removal, re-installation, and freight are not the responsibility of Maxxsonics, LLC. This warranty is limited to defective parts and specifically excludes any incidental or consequential damages connected therewith. To view the full warranty, please visit the website.

MB Quart products are designed and engineered in the USA by

MAXXSONICS®

www.maxxsonics.com